# **BULL DOZER**



MODEL: D60EX-15

## TECHNICAL SPECIFICATIONS



## MAIN SPECIFICATIONS

Operating weight: (kg) 10500

Overall Dimension (L xWxH): (mm) 4190x2935x3020

Track gauge: (mm) 1650

Min. Ground Clearance: (mm) 368

Max. gradeability: (%) 30

### ENGINE

Model: Cummins 4BTA3.9-C110

Rated Power: (HP) 110 Rated Speed: (rpm) 2200



Gear: 4 Forward, 2 Reverse Forward: (km/h) 2.6-10.4 Reverse: (km/h) 3.7-6.7

## TRANSMISSION

Torque Converter Type: Mechanical Power Shift Transmission

Transmission: Mechanical

Steering Clutch: Multi-disc, dry type Steering Brake: Floating brake

Final Drive: A pair of external meshing gear

## CABIN

An ergonomically designed sound proof cabin, enabling wide operational view, comes standard with designer upholstery, adjustable POWERPLUS air suspension driver's seat, streamline dashboard, air con and radio/mp3 player for extensive operations with well deserved comfort.

## HYDRAULIC SYSTEM

Pump type: Gear pump Max. pressure: (MPa) 16 Discharge: (L/min) 80



#### WORKING EQUIPMENT AND ATTACHMENT

Blade Type: Straight Tilt
Blade length: (mm) 2935
Blade height: (mm) 960
Dozing capacity: (m³) 2.8
Max. digging depth: (mm) 350
Max. lift height: (mm) 830

## UNDERCARRIAGE EQUIPMENT

Track shoes width: (mm) 450 Carrier rollers (each side): 1 Track rollers (each side): 6

Pitch: (mm) 171

No. of shoes (each side): 39

Optional: LGP Track

## OPTIONAL ATTACHMENT

Multi-shank Ripper Semi-U Blade U Blade

Angle Blade ROPS cabin Cold weather kit

Winch