



MINI EXCAVATOR

MODEL : PP60E-IX

TECHNICAL SPECIFICATIONS

POWERPLUS
POWERPLUS GROUP INC., USA

■ MAIN SPECIFICATIONS

Operating weight: (kg) 5750
Rated bucket capacity: (m³) 0.2
Overall length: (mm) 6065
Overall width: (mm) 1900
Overall height: (mm) 2590
Min. ground clearance: (mm) 340
Max. bucket digging force: (kN) 37.3
Rotating platform speed: (rpm) 11.5
Gradeability: (%) 60

■ WORKING RANGE

Max. digging radius: (mm) 6380
Max. digging height: (mm) 5700
Max. digging depth: (mm) 3935
Max. dumping height: (mm) 3855
Max. height digging radius: (mm) 4127
Max. dozing depth: (mm) 397
Max. dozing height: (mm) 251
Max. tail turning radius: (mm) 1670

■ ENGINE

Model: Yanmar 4TNV94L (Made in Japan)
Rated output: (HP) 50
Rated speed: (rpm) 2200
Emission: Euro III

■ UNDERCARRIAGE

Track length: (mm) 2455
Track ground length: (mm) 1910
Track gauge: (mm) 2458
Traction speed: (km/h) 2.66/4.25
Ground pressure: (kPa) 34
Track Roller: 2
Carrier Roller: 6

■ HYDRAULIC SYSTEM

Pump type: NACHI
Hydraulic flow: (l/min) 121
Auxiliary flow: (l/min) 50



■ CABIN

An ergonomically designed sound proof cabin, enabling wide operational view, comes standard with designer upholstery, adjustable POWERPLUS air suspension driver's seat, streamline dashboard, air con and radio/mp3 player for extensive operations with well deserved comfort.

■ DOZER BLADE

Width: (mm) 1865
Height: (mm) 376

■ TRACTION SYSTEM

Track: Rubber / Steel
Track width RT (ST): (mm) 400

■ OPTIONAL ATTACHMENT

Quick coupler
Hydraulic breaker