



MINI EXCAVATOR

MODEL : PP60S-IX

TECHNICAL SPECIFICATIONS

POWERPLUS
POWERPLUS GROUP INC., USA

■ MAIN SPECIFICATIONS

Operating weight: (kg) 5710
Rated bucket capacity: (m³) 0.20
Overall length: (mm) 5715
Overall width: (mm) 2000
Overall height: (mm) 2715
Min. ground clearance: (mm) 345
Max. bucket digging force: (kN) 25.7
Rotating platform speed: (rpm) 10.5
Gradeability: (%) 60

■ WORKING RANGE

Max. digging radius: (mm) 6360
Max. digging height: (mm) 5940
Max. digging depth: (mm) 3790
Max. dumping height: (mm) 4050
Max. height digging radius: (mm) 6370
Max. dozing depth: (mm) 460
Max. dozing height: (mm) 350
Max. tail turning radius: (mm) 1000

■ ENGINE

Model: Yanmar 4TNV94L (Made in Japan)
Rated output: (HP) 50
Rated speed: (rpm) 2100
Emission: Euro III

■ UNDERCARRIAGE

Track length: (mm) 2600
Track ground length: (mm) 2060
Track gauge: (mm) 2605
Traction speed: (km/h) 2.8/4.7
Ground pressure: (kPa) 31.6
Track Roller: 2
Carrier Roller: 6

■ HYDRAULIC SYSTEM

Main pump: NACHI (Made in Japan)
Hydraulic flow: (L/min) 121
Auxiliary flow: (L/min) 50



■ CABIN

An ergonomically designed sound proof cabin, enabling wide operational view, comes standard with designer upholstery, adjustable POWERPLUS air suspension driver's seat, streamline dashboard, air con and radio/mp3 player for extensive operations with well deserved comfort.

■ DOZER BLADE

Width: (mm) 1865
Height: (mm) 379

■ TRACTION SYSTEM

Track: Rubber / Steel
Track width RT (ST): (mm) 376

■ OPTIONAL ATTACHMENT

Quick Coupler
Hydraulic Breaker